



US008634894B2

(12) **United States Patent**  
**Rea et al.**

(10) **Patent No.:** **US 8,634,894 B2**  
(45) **Date of Patent:** **\*Jan. 21, 2014**

(54) **ELECTRODE FOR PROLONGED  
MONITORING OF LARYNGEAL  
ELECTROMYOGRAPHY**

(56) **References Cited**

U.S. PATENT DOCUMENTS

(71) Applicant: **Neurovision Medical Products, Inc.,**  
Ventura, CA (US)

3,326,207 A 6/1967 Egan  
4,461,304 A 7/1984 Kuperstein

(Continued)

(72) Inventors: **James Lee Rea**, Ventura, CA (US);  
**Stephen W. Blakely**, O'Fallon, MO  
(US)

FOREIGN PATENT DOCUMENTS

(73) Assignee: **Neurovision Medical Products, Inc.,**  
Ventura, CA (US)

WO WO2004/016438 2/2004  
WO WO2006/105121 10/2006

OTHER PUBLICATIONS

(\*) Notice: Subject to any disclaimer, the term of this  
patent is extended or adjusted under 35  
U.S.C. 154(b) by 0 days.

Shaw-Klein, L., "Material Selection When Printing Functional  
Traces on Medical Devices", EMEDT, p. 1-5, May 2010, Sep. 13,  
2010 <<http://www.emdt.co.uk/article/material-se>.

This patent is subject to a terminal dis-  
claimer.

(Continued)

(21) Appl. No.: **13/909,966**

*Primary Examiner* — Lee S Cohen

(22) Filed: **Jun. 4, 2013**

(74) *Attorney, Agent, or Firm* — Koppel, Patrick, Heybl &  
Philpott; Michael J. Ram

(65) **Prior Publication Data**

US 2013/0267817 A1 Oct. 10, 2013

(57) **ABSTRACT**

**Related U.S. Application Data**

(62) Division of application No. 12/887,427, filed on Sep.  
21, 2010, now Pat. No. 8,467,844.

(60) Provisional application No. 61/244,402, filed on Sep.  
21, 2009.

(51) **Int. Cl.**

**A61B 5/0492** (2006.01)

**H01R 43/00** (2006.01)

(52) **U.S. Cl.**

USPC ..... **600/380**; 600/393; 600/546; 29/825

(58) **Field of Classification Search**

CPC ..... A61B 5/0421; A61B 5/0492

USPC ..... 600/380

See application file for complete search history.

Laryngeal surface electrodes are devices designed to hold a  
conductive surface against the vocal cords in order to pick up  
small electrical signals from the muscle known as elec-  
tromyographic signals. Several embodiments of a laryngeal  
electromyography tube include a conductive electrode sur-  
face that is painted, screen printed or otherwise applied  
directly onto the body of an endotracheal tube, such that the  
final device has no raised surfaces which can injure the vocal  
cords. These endotracheal tube with integral laryngeal sur-  
face electrodes can be safely used placed for prolonged, con-  
tinuous monitoring during surgery, after surgery and during  
intensive care treatment intubation without a need to remove  
and replace the tube at these various stages of treatment. In  
one embodiment, one electrode contacts the vocal cords and  
a second electrode contacts the tongue.

**19 Claims, 6 Drawing Sheets**

